



8 PORT FIBER OPTIC FTTX BOX - MINI IP65 2 IN 8 OUT

FTTH, FTTx, GPON



Overview

Fiber access termination box is able to hold up to 8 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Applications

- Telecommunication Network
- CATV-Cable Television
- Wall-Mounted, Pole-Mounted, Aerial Application
- FTTH, FTTx, GPON

Features

2 inputs can use multi-fiber cable or uncut cable, 8 outputs for FTTH, convenient fast to operate.

The fiber bending radius minimum is 20mm.

Unique design of separate covers for the adapter and cable entry/exit ports to makes it more safety, nice and humanity, both cover is removable.

All the materials are non toxic and dermatologically safe, can last long for more than 20years.

Plastic material is flame retardant, metal parts is steel stainless AISI-303 and resistant to the corrosion in normal temperature, can be test ok in different facilities.

Specification

Color	Gray
Dimension (A*B*C) mm	170*130*40 (H*W*D)
Max. Capacity	8 cores
Max. Adapter	8 pcs SC simplex
PLC Splitter	1x2,1x4,1x8, 2x2, 2x4 mini splitter
Material	PC+ABS
Weight	0.5 kg

Pictures for reference

